



Model AS-240

Model AS-240



The Drop 'N Master™, Designed for the Needs of Coin Validation.

The AS-2 is field programmable for any coin or metal token up to 38mm in size without the need to exchange parts or make adjustments of any kind to the unit.

Features:

Programming is easily achieved with a single push of a button followed by the insertion of four coins of the same denomination. An additional option to this acceptor is a secondary security feature. With this option, the "Drop 'N Master" can only be reprogrammed by the individual with the security access. The AS-2 is capable of high-speed acceptance response with minimal rejection. The level of acceptance and rejection rate can be calibrated by adjusting the dial on the unit.

General Specifications:

- **Applicable Coin Range:**
Diameter: 17.9mm~38.0mm
Thickness: 1.3mm~2.8mm
- **Operating Temperature:**
0°C ~ +50°C
- **Operating Humidity:**
65%±20%
- **Operating Voltage:**
12VDC±5%
24VDC±5%
- **Power Consumption:**
50mA (idle)
Max. 320mA (peak at 24VDC)
- **Credit Output Signal:**
PNP Transition Active High
- **Inhibit Operation:**
Switch Selectable Active High or Low

- **Position in Use:**
Upright or within 2° in any direction

- **Weight (Approximate):**
0.53lbs.

Options:

- **Security Access Accessory**

