

CD-9603 Control Board



The ideal solution for dispensing credit card size paper or polyester cards (ISO7816). Designed with a new clutch and reverse roller, the CD-200 prevents double dispensing of cards or the dispensing of two cards stuck together.

Features:

- **CLUTCH SYSTEM & PATENTED REVERSE ROLLER**
This combination promises a stable card dispensing capability without error. The CD-200 can be utilized widely for various card dispensing applications.
- Available for a wide range of card thickness and materials.
- Industry Standard for Telecommunications & Transportation Applications.
- **COMPREHENSIVE CONTROL BOARD FOR EASY SYSTEM INTEGRATION**
This model is equipped with an


exclusive electronic control board for easy circuit operations. If the card feeding interval is too long (above 4 seconds) the reverse roller circuit will automatically operate and repeat the operation again. The number of times the operations is repeated can be selected with the dip switches.

General Specifications:

- **Applicable Card Sizes:**
Debit / Credit Cards*
53mm (min) ~ 58mm (max)
x 76mm (min) ~ 86mm (max)
Thickness: 0.15mm ~ 0.70mm
(.01" ~ .03")
**Cards with embossed characters can not be dispensed.*
- **Card Capacity:**
Holds approximately 200 Cards;
varies according to thickness.
- **Dispensing Speed:**
2 seconds per card.
High speed dispensing (approx. 1.2

seconds per card) is available upon request.

- **Supply Voltage Options:**
12VDC or 24VDC +/- 10%
- **Current Consumption:**
Operational - 1.50A (peak)
- **Operating Temperature:**
-10° C ~ 40° C with 30%-90% humidity.
- **Size:**
180mm (H) x 155mm (D)
x 93.2mm (W)
- **Weight:**
3.53lbs.



Custom models available please consult an Asahi Seiko Representative

