



Specifically designed for simple integration into a host machine; this product forms the total card handling solution for any system where cards are processed.


Features:

The MCE-2500 is the latest product to be developed in the MCE range and supersedes the MCE-2000. It incorporates all of the features of the previous versions with the addition of some new options.

- New short antenna for Mifare operation with customers own interface.
- New ACG Mifare module
- New ACG Legic module version
- The unit offers in its baseline form connection to a standard ISO-7816 IC card

General Functionality

- Accept contact or contactless IC cards for re-loading



- Automatically capture and retain stolen fraudulent or refunded cards accidentally left in the entry slot.
- Lock-out cards and maintain configuration during power interruptions.

General Specifications:

- **Host Control Interface:** Serial (RS-232) / Parallel
- **Supply Voltage Options:** 24VDC ± 15%
- **Current Consumption:** Operational – 250mA (average), 2.0A (peak)
Stand-by – 100mA (average), 600mA (peak)
- **Size:** 111mm (H) x 180mm (D) x 100mm (W)
- **Contactless IC Card Interface:** Serial (RS-232) or Direct (Antenna only version)

• **Contactless IC Card Connector Specification:**

Landing Type. Suits cards having contacts in accordance with ISO 7816

• **Applicable Contactless IC Cards:**

For ACG Mifare/Legic or antenna only versions of the MCE-2500, the following card type is suitable: ISO/IEC 14443 part 1-4, identification cards (contactless IC cards-Proximity type)

• **Environment:**

Temperature: -10°C ~ +40°C
Humidity: 30% ~ 90% (non condensing)

• **Stored Card Capacity:**

Up to 445 cards (1.8mm thick)

Custom models available please consult an Asahi Seiko Representative

