



AsahiSeiko
USA INC.

PRODUCT OVERVIEW

Coin & Card Handling Equipment

www.asahiseikousa.com

Introduction

Asahi Seiko was founded in 1969 with the aim of bringing innovative and high quality solutions to the market. After 45 years, with customers all over the world, our aim is still the same. We are focused on providing our customers with reliable products that complement their own machines.

This brief overview is to give you an idea of what Asahi Seiko has to offer in our ranges of coin and card handling devices. Our sales teams are available to offer further information on any product, contact details can be found at the back of this brochure.

- 04** SH Coin Hoppers
- 05** SA Coin Hoppers
- 06** FH Escalator Hoppers
- 07** SCH Escalator Hoppers
- 08** Large Coin Hoppers
- 09** Card Dispensers
- 10** IC Card Products
- 11** Coin Recyclers

SH-300



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 17.5-26.7mm
Thickness: 1.3-3.1mm
- ▶ **Dispensing Speed:**
Up to 600 coins per minute (approx)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter - 210 coins (approx)
- ▶ **Motor Control:**
Dedicated Control Board using CCTalk

SH-350



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 17.5-26.7mm
Thickness: 1.3-3.1mm
- ▶ **Dispensing Speed:**
Up to 600 coins per minute (approx)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter - 400 coins (approx)
- ▶ **Motor Control:**
Dedicated Control Board using CCTalk

SH-400



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 16.5-30.8mm
Thickness: 1.5-3.1mm
- ▶ **Dispensing Speed:**
Up to 600 coins per minute (approx)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter - 400 coins (approx)
- ▶ **Motor Control:**
Dedicated Control Board
Parallel or CCTalk

SA-595



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
 - Easy to change discs without the need for special tools or equipment.
 - Slide mount for easy removal
 - Built in motor brake and auto-reverse mechanism
- ▶ **Applicable Coin Size:**
Diameter: 16.25-30.8mm
Thickness: 1.3-3.2mm
- ▶ **Dispensing Speed:**
600 coins per minute (approximately)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter 400 coins
- ▶ **Motor Control:**
Parallel or CCTalk

SA-595 LC



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 16.25-28.5mm
Thickness: 1.5-3.2mm
- ▶ **Dispensing Speed:**
400 coins per minute (approximately)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter 400 coins
- ▶ **Motor Control:**
Parallel or CCTalk

FH-700/L1



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 20-26mm
Thickness: 1.5-2.5mm
- ▶ **Escalator Heights:**
365mm, 560mm (increasing in increments of 195mm)
- ▶ **Dispensing Speed:**
Up to 300 coins per minute
- ▶ **Motor Voltage:**
DC24V
- ▶ **Coin Capacity:**
Approximately 1000pcs of 20mm Coin

FH-700/L1D



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
This new escalator hopper features a flexible coin range with last coin payout, a diverter option is available to select coins as they are dispensed, meaning that this hopper can be used as part of a coin recycling system.

SCH-700/U1



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 21.0 to 28.6mm
Thickness: 1.7-3.2mm
- ▶ **Dispensing Speed:**
Up to 300 coins/minute
- ▶ **Coin Capacity:**
Up to 600 coins
23mm diameter

SCH-800/U1



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 21.0 to 28.6mm
Thickness: 1.7-3.2mm
- ▶ **Dispensing Speed:**
Up to 300 coins/minute
- ▶ **Coin Capacity:**
Up to 600 coins
23mm diameter

WH-3



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 24.3-39.0mm
Thickness: 1.6-3.3mm
- ▶ **Dispensing Speed:**
550 coins per minute (approximately)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
30.8mm diameter 550 coins
38.0mm diameter 220 coins
- ▶ **Motor Control:**
Dedicated Control Board

DH-750



TECHNICAL SPECIFICATIONS

- ▶ **Applicable Coin Size:**
Diameter: 17.9 - 38.0mm
Thickness: 1.5 - 3.2mm
- ▶ **Dispensing Speed:**
200 coins per minute (approximately)
- ▶ **Coin Capacity:**
Coin Size (example) Head Capacity
25mm diameter 1000 coins
(approximately)
- ▶ **Motor Control:**
Direct Motor Control, or DC motor
brake

CD-200



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
Features a built in card storage area
and is suitable for credit size cards
- ▶ **Applicable Cards:**
Paper or Polyester Credit card Size
- ▶ **Card Width:**
53.0 - 58.0mm
- ▶ **Card Length:**
76.0 - 86.0mm
- ▶ **Card Thickness:**
0.2 - 1.0mm

CD-1000



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
This unit has a range of cassettes to
store the cards,
it handles similar size cards
as the CD-200
- ▶ **Applicable Cards:**
Paper or Polyester Credit card Size
- ▶ **Card Width:**
52.0 - 56.0mm
- ▶ **Card Length:**
79.0 - 89.0mm
- ▶ **Card Thickness:**
0.2 - 1.0mm

CDMI-1000



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
Incorporates a manual
insertion reader with a
smart card dispenser
- ▶ **Applicable Cards:**
Polyester Credit card Size
- ▶ **Size:**
180mm(H) x 200mm(D) x 95mm(W)


SCD-2500



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
Dispense/Encode/Accept cards
Contact and contactless options
- ▶ **Supply Voltage Options:**
24V DC \pm 15%
- ▶ **Current Consumption:**
Operational: 250mA (average)
2.0A (peak)
Stand-by: 100mA (average) 600mA (peak)
- ▶ **Size:**
200mm(H) x 280mm(D) x 105mm(W)

MCE-2500



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
Accept and encode cards
Contact and contactless options
- ▶ **Supply Voltage Options:**
24V DC \pm 15%
- ▶ **Current Consumption:**
Operational: 250mA (average)
1.5A (peak)
Stand-by: 100mA (average) 600mA (peak)
- ▶ **Size:**
115mm(H) x 183mm(D) x 101mm(W)

MCH-3000



TECHNICAL SPECIFICATIONS

- ▶ **Features:**
Accept and encode cards
Contact and contactless options
- ▶ **Supply Voltage Options:**
24V DC \pm 10%
- ▶ **Current Consumption:**
Operational: 100mA (average)
2.0A (peak)
- ▶ **Size:**
78mm(H) x 197mm(D) x 92mm(W)

CRF-4USA

The CRF-4USA is a new coin recycler featuring bulk entry and 8 coin capability.



TECHNICAL SPECIFICATIONS

- ▶ **Key benefits:**
 - Cashier or Customer facing – The unit can be used in either configuration
 - Secure coin storage – Recycled coins are locked inside the unit
 - Fully accountable – Reducing the need for daily handling of coins
- ▶ **Key features of the CRF-4USA include:**
 - Bulk Coin Capacity: 50 Coins Bulk Insertion
 - Coin Accept Speed: 3 Coins / Second
 - Recycled Denominations: Eight (8) Denominations
 - Coin Output Speed: 12 coins in 2 Seconds



AsahiSeiko USA INC.



HEAD OFFICE

ASAHI SEIKO

Aoyama Tower Building, 2F, 2-24-15, Minami
Aoyama, Minato-Ku, Tokyo 107-0062 Japan

TEL: +81-3-3401-6181

FAX: +81-3-3401-1325



NORTH AMERICA

ASAHI SEIKO USA Inc

6644 Paradise Road, Las Vegas
Nevada 89119 USA

TEL: +1-702-260-6666

FAX: +1-702-260-6493



EUROPE

ASAHI SEIKO (EUROPE) LTD

Asahi House, North Farm Road,
Tunbridge Wells, Kent, TN2 3DR

TEL: +44 (0) 1892 518173

FAX: +44 (0) 1892 518174

EMAIL: sales@aseuro.co.uk

YOUR ASAHI SEIKO CONTACT: