

LCE-500+CD

Asahiseiko

Card Dispenser



The LCE-500+CD dispenses, encodes, then drop vends or captures contactless cards of credit card size, creating a simple but effective card handling solution.

Features

- Option for barcode or customer's own contactless reader
- Drop vend to customer or capture cards
- Low level sensing option
- Fast dispensing speed
- Serial RS-232 or parallel control options for dispenser and diverter
- Card capacity of up to 1,000 cards
- Compact size
- Robust construction

NEW
PRODUCT



TECHNICAL SPECIFICATIONS

Supply Voltage	24VDC +/- 10% (0.5V peak to peak max ripple)
Current Consumption	0.2 Amps (4.0 Amps peak)
Control Interface	Parallel or serial RS-232 operation
Size	525mm(H) x 222mm(D) x 114mm(W)
Environment	Temperature: 14°F to 104°F Humidity: 30-90% (non-condensing)
Card Capacity	1,000 cards (0.8mm thickness)
Dispensing Speed	Approximately 1 second
Mating Connector (Control)	Molex C-Grid III_type 24-way socket
Mating Connector (Mifare)	Standard '9' way D type

* Specifications are subject to change without notice

ASAHI SEIKO USA, Inc.

Asahi Seiko USA, Inc. 6644 Paradise Road, Las Vegas, Nevada 89119-3719
Phone: (702) 260-6666 Email: sales@asusainc.com

© Asahi Seiko USA, Inc.

www.asahiseikousa.com